



Marazzi Group S.r.l.
Viale Virgilio 30
41123 Modena


05


001MRZI

EN 14411:2012

**Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$,
for internal and external walls and floorings**


Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness < 7,5 mm Breaking strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1300 N
Slipperiness	See table attached
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed


	
Marazzi Group S.r.l. Viale Virgilio 30 41123 Modena 05 002MRZI	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $0,5\% < E_b \leq 3\%$, for internal and external walls and floorings	
Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness < 7,5 mm Breaking strength ≥ 700 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1100 N
Durability, for: - Internal use - External use: Freeze/thaw resistance	Passed Passed
Resistance to thermal shock	Passed

	
Marazzi Group S.r.l. Viale Virgilio 30 41123 Modena 05 003MRZI	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $3\% < E_b \leq 6\%$, for internal walls and floorings	
Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness < 7,5 mm Breaking strength ≥ 600 N Thickness $\geq 7,5$ mm Breaking strength ≥ 1000 N
Durability, for: - Internal use	Passed

CE	
Marazzi Group S.r.l. Viale Virgilio 30 41123 Modena 05 004MRZI	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $6% < E_b \leq 10%$, for internal walls	
Reaction to fire	Class A1
Durability, for: - Internal use	Passed

CE	
Marazzi Group S.r.l. Viale Virgilio 30 41123 Modena 05 005MRZI	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption $E_b > 10%$, for internal walls	
Reaction to fire	Class A1
Durability, for: - Internal use	Passed

	
Marazzi Group S.r.l. Viale Virgilio 30 41123 Modena 05 006MRZI	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption 3% <Eb ≤ 6%, for internal walls	
Reaction to fire	Class A1
Durability, for: - Internal use	Passed

	
Marazzi Group S.r.l. Viale Virgilio 30 41123 Modena 05 007MRZI	
EN 14411:2012 Dry-pressed ceramic tiles, with water absorption Eb >10%, for internal walls and floorings	
Reaction to fire	Class A1 _{FL} /A1
Breaking strength	Thickness < 7,5 mm Breaking strength ≥ 200 N Thickness ≥ 7,5 mm Breaking strength ≥ 600 N
Durability, for: - Internal use	Passed