

WOOD EFFECT

Woodtale XT20 Collection

RAGNO 





R51W Woodtale Xt20 Miele Rt 40x120cm

Woodtale XT20

Woodtale XT20 is a wood-look stoneware produced in the 60x60 and 40x120 size with thickness 20 mm. Suitable for installation outdoors resting on grass, gravel and sand, glued on driveways and as a raised paving for public and private spaces.



R4XJ Woodtale Xt20 Noce Rettificato 60x60cm






R51W Woodtale Xt20 Miele Rt 40x120cm

Colorbody Fine Porcelain Stoneware




Betulla

| Size | Superficie | Code | Description | Thikness | Rett. | Caratteristiche tecniche | Use | R | BCR | Pendulum Class | Pend. PTV >36 | Australian pendulum | DCOF | Destinazioni d'uso | V | Premium Tech. | Scatole | Mq | Kg | Pallet | Mq | Kg |
|----------|--------------------|------|--------------------------|----------|-------|--------------------------|-----|------|--------|----------------|---------------|---------------------|---------|--------------------|----|---------------|---------|------|-------|--------|-------|----------|
| 40x120cm | Structured Surface | R51V | Woodtale Xt20 Betulla Rt | MM 20 | • | | | R11B | > 0.40 | Class 3 | 36+ Slider 96 | | >= 0.60 | H | V3 | | 1 | 0,48 | 21,43 | 48 | 23,04 | 1.028,57 |




Miele

| Size | Superficie | Code | Description | Thikness | Rett. | Caratteristiche tecniche | Use | R | BCR | Pendulum Class | Pend. PTV >36 | Australian pendulum | DCOF | Destinazioni d'uso | V | Premium Tech. | Scatole | Mq | Kg | Pallet | Mq | Kg |
|----------|--------------------|------|---------------------------------|----------|-------|--------------------------|-----|------|--------|----------------|---------------|---------------------|---------|--------------------|----|---------------|---------|------|-------|--------|-------|----------|
| 60x60cm | Structured Surface | R4XG | Woodtale Xt20 Miele Rettificato | MM 20 | • | | | R11B | > 0.40 | Class 3 | 36+ Slider 96 | | >= 0.60 | H | V3 | | 2 | 0,72 | 31,77 | 32 | 23,04 | 1.016,77 |
| 40x120cm | Structured Surface | R51W | Woodtale Xt20 Miele Rt | MM 20 | • | | | R11B | > 0.40 | Class 3 | 36+ Slider 96 | | >= 0.60 | H | V3 | | 1 | 0,48 | 21,31 | 48 | 23,04 | 1.023,09 |



Nocciola



| Size | Superficie | Code | Description | Thikness | Rett. | Caratteristiche tecniche | Use | R | BCR | Pendulum Class | Pend. PTV >36 | Australian pendulum | DCOF | Destinazioni d'uso | V | Premium Tech. | Scatole | Mq | Kg | Pallet | Mq | Kg |
|----------|--------------------|------|------------------------------------|----------|-------|--------------------------|-----|------|--------|----------------|---------------|---------------------|---------|--------------------|----|---------------|---------|------|-------|--------|-------|----------|
| 60x60cm | Structured Surface | R4XH | Woodtale Xt20 Nocciola Rettificato | MM 20 | • | | | R11B | > 0.40 | Class 3 | 36+ Slider 96 | | >= 0.60 | H | V3 | | 2 | 0,72 | 32,40 | 32 | 23,04 | 1.036,90 |
| 40x120cm | Structured Surface | R51X | Woodtale Xt20 Nocciola Rt | MM 20 | • | | | R11B | > 0.40 | Class 3 | 36+ Slider 96 | | >= 0.60 | H | V3 | | 1 | 0,48 | 21,27 | 48 | 23,04 | 1.020,82 |



Noce

| Size | Superficie | Code | Description | Thikness | Rett. | Caratteristiche tecniche | Use | R | BCR | Pendulum Class | Pend. PTV >36 | Australian pendulum | DCOF | Destinazioni d'uso | V | Premium Tech. | Scatole | Mq | Kg | Pallet | Mq | Kg |
|----------|--------------------|------|--------------------------------|----------|-------|--------------------------|-----|------|--------|----------------|---------------|---------------------|---------|--------------------|----|---------------|---------|------|-------|--------|-------|----------|
| 60x60cm | Structured Surface | R4XJ | Woodtale Xt20 Noce Rettificato | MM 20 | • | | | R11B | > 0.40 | Class 3 | 36+ Slider 96 | | >= 0.60 | H | V3 | | 2 | 0,72 | 31,90 | 32 | 23,04 | 1.020,82 |
| 40x120cm | Structured Surface | R51Y | Woodtale Xt20 Noce Rt | MM 20 | • | | | R11B | > 0.40 | Class 3 | 36+ Slider 96 | | >= 0.60 | H | V3 | | 1 | 0,48 | 21,36 | 48 | 23,04 | 1.025,37 |

Caratteristiche Tecniche

-  Frost proof
-  Resistance deep abrasion

Destinazioni d'uso

D
 Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
 Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
 Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

Variazioni cromatiche

V0
 Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
 Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
 Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run



















G
 Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.


H
 Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

V3
 Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
 Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni

| | | | | | | | |
|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |
| ISO 14001 | ISO 9001 | Green Building Council | GPP | EPD Italy | ISO 17889-1 | Greenguard | LEED Credits |
|  |  |  |  |  |  |  |  |
| QBUPEC F+ | FDES | Declare | HPD | CAM Sassuolo | CCC | CE 001MRZI | CE 005MRZI |
|  |  | | | | | | |
| UKCA 00 1MRZUK | SASO | | | | | | |



© Copyright by Ragno – Marazzi Group S.r.l. 2024. All Rights Reserved Marazzi Group Srl a Socio Unico Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@ragno.it
www.ragno.it

The Company reserves the right, at any time and without prior notice, to change the information and technical characteristics given in this catalogue, none of which are to be considered legally binding. Weights, colours and dimensions are subject to the normal variations resulting from the ceramic firing process. Within the limits of printed material, the colours and aesthetic features of the products illustrated correspond as closely as possible to those of the actual products.

PDF GENERATED AUTOMATICALLY ON 17/04/2026

RAGNO 