

WOOD EFFECT

# Woodtale XT20 Collection

RAGNO 





R51W Woodtale Xt20 Miele Rt 40x120cm

## Woodtale XT20

Woodtale XT20 is a wood-look stoneware produced in the 60x60 and 40x120 size with thickness 20 mm. Suitable for installation outdoors resting on grass, gravel and sand, glued on driveways and as a raised paving for public and private spaces.



R4XJ Woodtale Xt20 Noce Rettificato 60x60cm






R51W Woodtale Xt20 Miele Rt 40x120cm

Colorbody Fine Porcelain Stoneware




**Betulla**

Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
40x120cm	Structured Surface	R51V	Woodtale Xt20 Betulla Rt	MM 20	•			R11B	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V3		1	0,48	21,43	48	23,04	1.028,57




**Miele**

Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
60x60cm	Structured Surface	R4XG	Woodtale Xt20 Miele Rettificato	MM 20	•			R11B	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V3		2	0,72	31,77	32	23,04	1.016,77
40x120cm	Structured Surface	R51W	Woodtale Xt20 Miele Rt	MM 20	•			R11B	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V3		1	0,48	21,31	48	23,04	1.023,09



**Nocciola**



Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
60x60cm	Structured Surface	R4XH	Woodtale Xt20 Nocciola Rettificato	MM 20	•			R11B	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V3		2	0,72	32,40	32	23,04	1.036,90
40x120cm	Structured Surface	R51X	Woodtale Xt20 Nocciola Rt	MM 20	•			R11B	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V3		1	0,48	21,27	48	23,04	1.020,82



**Noce**

Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
60x60cm	Structured Surface	R4XJ	Woodtale Xt20 Noce Rettificato	MM 20	•			R11B	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V3		2	0,72	31,90	32	23,04	1.020,82
40x120cm	Structured Surface	R51Y	Woodtale Xt20 Noce Rt	MM 20	•			R11B	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V3		1	0,48	21,36	48	23,04	1.025,37

Caratteristiche Tecniche

-  Frost proof
-  Resistance deep abrasion

Destinazioni d'uso

**D**  
 Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

**E**  
 Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

**F**  
 Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

Variazioni cromatiche

**V0**  
 Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

**V1**  
 Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

**V2**  
 Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run



















**G**  
 Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.


**H**  
 Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

**V3**  
 Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

**V4**  
 Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni

							
ISO 14001	ISO 9001	Green Building Council	GPP	EPD Italy	ISO 17889-1	Greenguard	LEED Credits
							
QBUPEC F+	FDES	Declare	HPD	CAM Sassuolo	CCC	CE 001MRZI	CE 005MRZI
							
UKCA 00 1MRZUK	SASO						



© Copyright by Ragno – Marazzi Group S.r.l. 2024. All Rights Reserved Marazzi Group Srl a Socio Unico Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy  
T +39 0536 860800 F +39 0536 860644  
info@ragno.it  
www.ragno.it

The Company reserves the right, at any time and without prior notice, to change the information and technical characteristics given in this catalogue, none of which are to be considered legally binding. Weights, colours and dimensions are subject to the normal variations resulting from the ceramic firing process. Within the limits of printed material, the colours and aesthetic features of the products illustrated correspond as closely as possible to those of the actual products.

PDF GENERATED AUTOMATICALLY ON 10/04/2026

**RAGNO** 