

STONE LOOK

Kalkstone XT20 Collection



Kalkstone XT20

Structured surfaces with high slip resistance, thanks to the StepWise technology which ensures excellent technical performance while conserving a soft-touch "feel". All the beauty of stone is expressed in outdoor spaces where multi-size installation patterns underline the free flow of delicate veining. 60x120 cm slabs with thickness of 20 mm complete a product range suitable for any location, residential or commercial.



RALD Kalkstone Xt20 Sand Rt 60x120cm

Colorbody Fine Porcelain Stoneware




Grey

Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
60x120cm	Structured Surface	RALG	Kalkstone Xt20 Grey Rt	MM 20	•			R11C	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V2		1	0,72	32,42	36	25,92	1.167,04



Natural


Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
60x120cm	Structured Surface	RALF	Kalkstone Xt20 Natural Rt	MM 20	•			R11C	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V2		1	0,72	32,04	36	25,92	1.153,54





Sand

Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
60x120cm	Structured Surface	RALD	Kalkstone Xt20 Sand Rt	MM 20	•			R11C	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V2		1	0,72	31,99	36	25,92	1.151,49



Colorbody Fine Porcelain Stoneware



White

Size	Superficie	Code	Description	Thikness	Rett.	Caratteristiche tecniche	Use	R	BCR	Pendulum Class	Pend. PTV >36	Australian pendulum	DCOF	Destinazioni d'uso	V	Premium Tech.	Scatole	Mq	Kg	Pallet	Mq	Kg
60x120cm	Structured Surface	RALC	Kalkstone Xt20 White Rt	MM 20	•			R11C	> 0.40	Class 3	36+ Slider 96		>= 0.60	H	V2		1	0,72	32,14	36	25,92	1.157,14

Caratteristiche Tecniche

-  Frost proof
-  Resistance deep abrasion

Destinazioni d'uso

D
 Tiles suitable only for residential bathrooms and bedrooms; any type of abrasion must be avoided.

E
 Tiles suitable for any room of a house except for entrance areas and kitchens. Low stress abrasive wear.

F
 Tiles suitable for any room of a house without direct access from the outside or access not protected by doormats. Average stress abrasive wear.

Variazioni cromatiche

V0
 Monochromatic - V0: tiles of the same shade are very uniform, in just one colour

V1
 Uniform appearance - V1: uniform colour with only minimal differences between tiles in the same production run

V2
 Slight variation - V2: clearly distinguishable differences in texture and pattern within the same production run





















G
 Materials suitable for rooms subject to medium-heavy abrasion, such as detached houses and light-traffic commercial buildings.

H
 Materials suitable for situations of relatively hard abrasion in environments without protection against scratching, both public and private.

V3
 Moderate variation - V3: significant variation in texture, pattern and colour from tile to tile within the same production run. The colour range should be viewed before selecting the material

V4
 Substantial/random variation - V4: random differences from tile to tile. One tile may have totally different texture and colour from another. The colour range should be viewed before selecting the material

Certificazioni

 CQY CERTIFICAZIONE SISTEMA DI GESTIONE AMBIENTALE UNI EN ISO 14001:2015	 CQY CERTIFICAZIONE SISTEMA DI GESTIONE AMBIENTALE UNI EN ISO 14001:2015	 CQY CERTIFICAZIONE SISTEMA DI GESTIONE DELLA SICUREZZA UNI EN ISO 45001:2018	 CQY CERTIFICAZIONE SISTEMA DI GESTIONE QUALITÀ UNI EN ISO 9001:2015				
ISO 14001	ISO 50001	ISO 45001	ISO 9001	Green Building Council	GPP	EPD Italy	ISO 17889-1
							
Greenguard	LEED Credits	QBUPEC F+	FDES	Declare	HPD	CAM Sassuolo	CAM Fiorano
							
CCC	CE 001MRZI	UKCA 00 1MRZUK	SASO				

© Copyright by Ragno – Marazzi Group S.r.l. 2024. All Rights Reserved Marazzi Group Srl a Socio Unico Viale Regina Pacis, 39 41049 Sassuolo (MO) Italy
T +39 0536 860800 F +39 0536 860644
info@ragno.it
www.ragno.it

The Company reserves the right, at any time and without prior notice, to change the information and technical characteristics given in this catalogue, none of which are to be considered legally binding. Weights, colours and dimensions are subject to the normal variations resulting from the ceramic firing process. Within the limits of printed material, the colours and aesthetic features of the products illustrated correspond as closely as possible to those of the actual products.

PDF GENERATED AUTOMATICALLY ON 10/04/2026

RAGNO 